

## BRAVO 3250 BT



### Standard equipment:



- 2 x 5.511.1789  
PPL Brush Ø 330 mm - 13"



- 4.508.1619  
Front squeegee blade  
L.960 mm Th. 2,5 mm

- 4.508.1618  
Rear squeegee blade  
L.1000 mm Th. 3 mm



- 0.108.0054  
On-board Battery charger  
CBH2D 24V 20A  
(only for models code:  
8.579.0002 - 8.579.0011)

Designed for the maintenance and deep cleaning of large areas (up to 3200 m<sup>2</sup>.) with a very important reduction of cleaning cost. Very compact size and great maneuverability like walk behind models: suited for maintenance cleaning. • 32 kg. of constant pressure on the brushes. • Double counter rotating brush (66 cm of scrubbing width) obtaining better stability and constant pressure. • Great working autonomy thanks to the possibility to use 4 batteries 6 V 240 Ah and to rear wheel-drive. • Large load tank capacity (real load of 75 l. ), resulting in reduced numbers of stops and maximum use of battery for effective operation of the machine. • Ergonomic steering wheel of new design with user friendly controls and digital display. • Easy access to electrical components. • Inspection cover for fast and easy cleaning and sanification of dirt water tank. • Automatic device that stops brushes and detergent water outflow when the machine is stationary. • Self-levelling brush plate. • **Automatic detergent measuring system.**

	BRAVO 3250 BT
code	
power supply	24V (battery charger included)
scrubbing / squeegee width	660 / 855 mm
max working capacity	3250 m <sup>2</sup> /h
detergent tank capacity	75 l / 19.81 gal
recovery tank capacity	75-80 l / 19.81-21.13 gal
traction	rear wheel-drive / 400 W
RPM / pressure on the brushes	170/32 kg / 70.54 lbs
brush motor power	2 X 400 W
max gradient empty/full tank	13% / 10%
depression / vacuum motor	1300 mmH <sub>2</sub> O/400 W
dimensions / weight	123 x 63 h 121 cm /162 kg



Great working autonomy thanks to the possibility to use 4 batteries 6 V 240 Ah granting continuous working up. Possibility to use also 2 batteries 12V. Less battery consumption thanks to rear wheel-drive. Large load tanks made of shock and acid proof polyethylene (real load of 75 l. ), avoiding frequent stop for refilling.

## Optional accessories:



- 4 x 0.107.0004  
Tubular battery Pb-acid  
6V 180Ah C5



- 4 x 0.107.0072  
Gel battery 6 MFP 180  
6V 180Ah C5



- 2 x 0.107.0002  
Tubular battery Pb-acid  
12V 118 Ah C5



- 0.108.0002  
Battery charger 24V 25A  
220-240/50-60



- 4.508.1594 Polyurethane  
front blade L.960 TH.3 Sh.40
- 4.508.1596 Polyurethane  
rear blade L.1000 TH.4  
Sh.40



- 2 x 5.511.1106  
Tynex brush Ø 330 mm-13"
- 2 x 5.511.1255  
PPL 0,03 brush Ø 330 mm-13"
- 2 x 5.511.1202  
PES brush Ø 330 mm - 13"



- 2 x 5.511.1107  
EWU pad driver  
Ø 330 mm-13"



- 2 x 6.508.0030 - Ø 340  
mm - 13"- beige (5 pcs.)
- 2 x 6.508.0037 - Ø 340  
mm - 13"- green (5 pcs.)
- 2 x 6.508.0044 - Ø 340  
mm - 13"- black (5 pcs.)



- 6.505.0062  
Flashing beacon

User friendly control panel. Steering wheel with digital controls and display. Squeegee and brush plate mechanical and user friendly lifting lever: min. maintenance cost training time for the users. Scrubbing unit with double brush with brush plate made of steel for a great pressure (32 Kg.) on the floor resulting in an easy and deep cleaning of any kind of dirt.



Rear wheel-drive on 2 wheels allows the machine to get over remarkable slopes. Detergent solution is cleansed by an external completely accessible filter, that holds any impurities, thus protecting the solenoid valve. The easy access to all internal components of XXS make it possible to reduce maintenance cost.

The comfortable and ergonomic seat allows the operator to work effortless for a long time, improving productivity. Its very compact size make it perfect to work in small areas where walk behind models are usually used. The use of XXS makes working easier and quicker with a huge saving of time.

