



## **Standard equipment:**



• 5.511.1097 PPL brush Ø 483 mm - 19"



• 4.508.X468 Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm • 4.508.X467

Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



• 0.108.0042 On-board Battery charger CBHD1 24V 10A only for model code: 8.527.0001 - 8.527.0002 8.527.0010 - 8.527.0012









• Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m²) • Especially suitable for cleaning: car shops, sales points, gym, health care • Control panel with operator presence safety system • Low level battery indicator: brush/vacuum and traction progressive cut off • Solution water filter and solenoid valve (battery model only) • Easy access to the battery compartment • Quick drain and easily inspectable recovery tank • Non-marking wheels • Roto-molded polyethylene tanks, shock and acid resistant • The lower tank also serves as battery compartment • Low noise operation thanks to the protected positioning of vacuum motor.

	HYPER 2000 E	HYPER 2000 B
code	8.527.0038	8.527.0037
power supply	230V	24V (battery charger included)
scrubbing / squeegee width	500 / 800 mm	500 / 800 mm
max working capacity	2000 m²/h	2000 m²/h
detergent tank capacity	44   / 11,63 gal	44   / 11,63 gal
recovery tank capacity	50-60 l / 13,21-16 gal	50-60 l/13,21-16 gal
traction	mechanical	mechanical
RPM / pressure on the brushes	150/20 kg /44,09 lbs	150/18 kg /44,09 lbs
brush motor power	550W	550W
detergent solution system	solenoid valve	solenoid valve
depression / vacuum motor	1700 mmH <sub>2</sub> O/1000W	1280 mmH <sub>2</sub> O/400W
dimensions / weight	116x46x98cm / 115 kg	116x51x98cm / 116 kg






Powerful gearmotor; metal brush plate with integrated plastic splash guard/bumper.

The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow when the brush is stopped during the interruptions of work.





Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the squeegee is released without any damage in the event of accidental impact.

Easy and intuitive controls. The outflow of the cleaning solution is easily controlled using the mechanical lever placed on the control panel. Inspectable mesh filter to trap any existing solid body in the cleaning solution.



## **Optional accessories:**



• 2 x 0.107.0002 Tubular battery Pb-acid 12V 118Ah C5



• 2 x 0.107.0063 GEL Battery 12 MFP 105 12V 105Ah C5



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 4



• 5.511.1098 Tynex brush Ø 483 mm-19" • 5.511.1128 PPL 0,03 brush Ø 483 mm-19" • 5.511.1206 PES brush Ø 483 mm - 19"



• 5.511.1099 EWU pad driver Ø 483 mm-19"



- 6.508.0034 Abrasive pad Ø 483 mm-19"
- beige (5 pcs.) • 6.508.0041
- Abrasive pad Ø 483 mm-19"
- green (5 pcs.)
- 6.508.0048
- Abrasive pad Ø 483 mm-19"
- black (5 pcs.)



4.512.0068 Extension electric cord 15 m with Schuko plug