

Tucson single-phase




Standard equipment:

- 3.700.0036 Gun M22 - 3/8.



- 3.701.0027 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 LP)
- 3.103.0047 Nozzle type 030 (mod. 1509 LP)



- 4.618.0049 High pressure hose 8 m



- Power cable 5 m

Available versions:

Code: **8.671.0005**
 Tucson 1509 LP **with hose reel** (10 m high pressure hose code 4.618.0053)

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons, brass linear pump head with built-in by-pass valve.
- Suction and delivery S. S. valves.
- Detergent built-in tank for indirect suction (2,8 lt.).
- Pressure regulator.
- Glycerine pressure gauge.
- Hose-reel **(optional)**.

| | Tucson 1211 LP | Tucson 1509 LP |
|------------------------------|-----------------------------|-----------------------------|
| code | 8.671.0001 | 8.671.0002 |
| operat. pressure/max | 120/150 bar-1740/2175 psi | 150/160 bar-2175/2320 psi |
| delivery rate | 660 l/h-2.91 GPM | 540 l/h-2.37 GPM |
| abs. power/voltage | 3000W - 230V~50Hz 1 ph | 3000W - 230V~50Hz 1 ph |
| motor/pump type/RPM | MP4/1450 RPM | MP4/1450 RPM |
| max. water inlet temperature | 40 °C | 40 °C |
| dimension/weight | 76x41x75cm/33 kg - 72,6 lbs | 76x41x75cm/33 kg - 72,6 lbs |